



TECHNICAL SPECIFICATIONS

Pneumatic Forklift Trucks

D20S / D25S / D30S / D33S-5 & D35C-5
 G20E / G25E / G30E-5
 G20P / G25P / G30P / G33P-5 & G35C-5
 For Europe



D/G 33S(P)-5

Mast type	Maximum Fork Height	Maximum Lowered Height	Fully Extended Height	Free Lift	Rated Load Capacities								
					D/G 33S(P)-5								
					Tilt Angle						Load Capacities		
With Load Backrest		With Load Backrest		Single Pneu.		Double Pneu.		Single Solid		Single Pneu.	Double Pneu.	Single Solid	
mm		mm		deg		deg		deg		LC 500mm	LC 500mm	LC 500mm	
STD	2030	1565	3290	152	6	10	6	10	6	10	3250	3250	3250
	2580	1840	3840	152	6	10	6	10	6	10	3250	3250	3250
	2950	2025	4210	152	6	10	6	10	6	10	3250	3250	3250
	3230	2165	4490	152	6	10	6	10	6	10	3250	3250	3250
	3500	2415	4765	152	6	10	6	10	6	10	3250	3250	3250
	3800	2565	5065	152	6	10	6	10	6	10	3250	3250	3250
	3950	2640	5215	152	6	10	6	10	6	10	3175	3250	3250
	4350	2840	5615	152	6	5	6	10	6	10	3175	3250	3250
4960	3140	6215	152	6	3	6	10	6	8	2450	3125	3200	
FF	2580	1840	3840	640	6	10	6	10	6	10	3250	3250	3250
	2950	2025	4210	825	6	10	6	10	6	10	3250	3250	3250
	3230	2165	4490	965	6	10	6	10	6	10	3250	3250	3250
	3600	2415	4865	1215	6	10	6	10	6	10	3250	3250	3250
FFT	3900	1890	5165	690	6	8	6	8	6	8	3250	3250	3250
	4290	2025	5570	825	6	5	6	8	6	8	3250	3250	3250
	4730	2165	5990	965	6	3	6	8	6	8	2900	3175	3250
	5560	2515	6815	1315	6	3	6	8	6	5	1750	2975	3050
	6010	2665	7265	1465	6	3	6	5	6	3	1350	2875	2950

D/G 35C-5

Mast type	Maximum Fork Height	Maximum Lowered Height	Fully Extended Height	Free Lift	Rated Load Capacities								
					D/G 35C-5								
					Tilt Angle						Load Capacities		
With Load Backrest		With Load Backrest		Single Pneu.		Double Pneu.		Single Solid		Single Pneu.	Double Pneu.	Single Solid	
mm		mm		deg		deg		deg		LC 500mm	LC 500mm	LC 500mm	
STD	1800	1565	3060	152	6	10	6	10	6	10	3500	3500	3500
	2350	1840	3610	152	6	10	6	10	6	10	3500	3500	3500
	2720	2025	3980	152	6	10	6	10	6	10	3500	3500	3500
	3000	2165	4260	152	6	10	6	10	6	10	3500	3500	3500
	3495	2415	4760	152	6	10	6	10	6	10	3500	3500	3500
	3655	2565	4915	152	6	10	6	10	6	10	3500	3500	3500
	3805	2640	5065	152	6	10	6	10	6	10	3500	3500	3500
	4205	2840	5465	152	6	8	6	10	6	10	3425	3425	3500
4805	3140	6065	152	6	3	6	8	6	8	3250	3275	3375	
FF	2350	1840	3610	640	6	10	6	10	6	10	3500	3500	3500
	2720	2025	3980	825	6	10	6	10	6	10	3500	3500	3500
	3000	2165	4260	965	6	10	6	10	6	10	3500	3500	3500
	3495	2415	4755	1215	6	10	6	10	6	10	3500	3500	3500
FFT	3555	1890	4815	690	6	8	6	8	6	8	3400	3400	3400
	3960	2025	5220	825	6	8	6	8	6	8	3400	3400	3400
	4380	2165	5640	965	6	5	6	8	6	8	3375	3375	3400
	4820	2335	6085	1135	6	3	6	8	6	8	3250	3250	3350
	5205	2515	6465	1315	6	3	6	8	6	5	2600	3150	3250
	5655	2665	6915	1465	6	3	6	5	6	3	1975	3050	3150



G20E / G25E / G30E-5
 G20P / G25P / G30P / G33P-5 & G35C-5
 2,000kg 2,500kg 3,000kg 3,300kg 3,500kg
 LP, Pneumatic Tire

D20S / D25S / D30S / D33S-5 & D35C-5
 2,000kg 2,500kg 3,000kg 3,300kg 3,500kg
 Diesel, Pneumatic Tire



PSC0911B2 (Dec 2014)



Head Office : 7-11, Hwasu-Dong, Dong-Gu, Incheon, Korea.
 Seoul Office : 22nd floor, Doosan Tower Bldg, Euljiro 6-Ga
 Jung-Gu, Seoul, Korea.
 Tel : 82-2-3398-8632 Fax : 82-2-3398-8619

AUTHORIZED DEALER

Product and specifications are subject to improvement and change without notice.