

LIFTING INNOVATION

C6,000 GT

The multi-directional forklift designed for the safe, space saving and productive handling of long and bulky loads.











REF.	DESCRIPTION	C6,000 GT						
1a	Lift Height	248"						
1b	Free Lift Height	104"						
2	Height Mast Closed	157″						
3	Max. Mast Raised	303"						
4	Overall Length	50"	56"	62"	68"	74"	80"	86"
5	Mast travel	26"	32"	38"	44"	50"	56"	62"
6	Ground Clearance Under Mast	5″						
7	Ground Clearance to Center of Wheelbase	5″						
8	Height Over Cab (without work lights)	114"						
9	Width Across Platforms	116″						
10	Outside Spread of Fork Arms	131½″						
11	Wheelbase	901/2"						
12	Frame Opening	55"						
13	Load Center Distance	12"	15"	18"	21"	24"	24"	24"
14	Overhang Front				6"			
15	Track	38"	44"	50"	56"	62"	68"	74"
16	Overhang Back	6"						
17	Length from Face of Fork	26"						
18	Forward Tilt	3°						
19	Backward Tilt	4½°						
20	Platform Height (with front lowered)	161/2"						
21	Platform Length	24"	30"	36"	42"	48"	54"	60"
Α	Capacity	6,000 lbs						
В	Unladen Weight	18,000 lbs	18,500 lbs	19,000 lbs	19,500 lbs	20,000 lbs	20,500 lbs	21,000 lbs
С	Maximum Ground Speed	7½ mph						
D	Gradeability	10%						
Е	3 ltr GM LPG	65 HP						
F	Electrics	12 Volt						
G	Fork Section 2" x 6" x	24"	30"	36"	42"	48"	54"	60"
Н	350 / 150 - 280 Front Tire (Solid) x2	OD 14" / Width 6"						
- 1	16 x 7 - 12 Rear Tire (Super Elastic) x2	OD 23" / Width 10"						
J	Standard Color	Green & Gray						







Features Include:

- Rubber Mounted Overhead Guard
- Load Sensing Steering
- Tilting Chassis +/- ½" at front
- 4 Wheel Steering
- 2 Wheel Hydrostatic Drive
- Hydraulic Oil Cooler

Distributed by:

303 Concord Street, Greensboro, North Carolina 27406 Toll free: 1-877 COMBI 56

Tel: 336-378-8884 info@combilift.com

Combilift has a policy of continuous product development and reserves the right to alter specifications without prior notice. Specifications and/or dimensions may vary from those illustrated in some countries.